

QUAD COMBINATION REAR LAMPS



5 year warranty

12/24V

IP67

Voltage Range: 12/24V

Warranty: 5 years

Ingress Protection: IP67

Approval: ECE & EMC ✓

- 100mm square lamp modules
- Black quad surface mounting bracket
- Tough acrylic lenses
- Shock, water & dust proof

- Replacement lamp modules available; 100AMEB, 100RMEB, 100WMEB, 100FMEB
- Replacement bracket available; 100B4B



STOP / TAIL / INDICATOR / REVERSE

100BRAWME

Current Draw (13.8V / 28V):
 Stop: 0.38A / 0.24A, Tail: 0.04A / 0.07A,
 Indicator: 0.38A / 0.23A,
 Reverse: 0.31A / 0.17A



STOP / TAIL / INDICATOR / FOG

100BFARRME

Current Draw (13.8V / 28V):
 Stop: 0.38A / 0.24A, Tail: 0.04A / 0.07A,
 Indicator: 0.38A / 0.23A, Fog: 0.42A / 0.21A



STOP / TAIL / INDICATOR / REVERSE / FOG

100BFWARME

Current Draw (13.8V / 28V):
 Stop: 0.38A / 0.24A, Tail: 0.04A / 0.07A,
 Indicator: 0.38A / 0.23A, Fog: 0.42A / 0.21A,
 Reverse: 0.31A / 0.17A



STOP / TAIL / INDICATOR

100BAARRME

Current Draw (13.8V / 28V):
 Stop: 0.38A / 0.24A, Tail: 0.04A / 0.07A,
 Indicator: 0.38A / 0.23A



STOP / TAIL / INDICATOR / REVERSE / FOG

100BSTI2WFMLE

Current Draw (13.8V / 28V):
 Stop: 0.38A / 0.24A, Tail: 0.04A / 0.07A,
 Indicator: 0.38A / 0.23A, Fog: 0.42A / 0.21A,
 Reverse: 0.31A / 0.17A



STOP / TAIL / INDICATOR / REVERSE / FOG

100BSTI2WFMRE

Current Draw (13.8V / 28V):
 Stop: 0.38A / 0.24A, Tail: 0.04A / 0.07A,
 Indicator: 0.38A / 0.23A, Fog: 0.42A / 0.21A,
 Reverse: 0.31A / 0.17A

Overall Size: 430 x 125 x 50mm
 Cable Length: 400mm

