



This beacon is part of a range of LED warning beacons, which feature a dual-voltage SMD LED array with selectable flash patterns.

- ◆ Dual-voltage operation (12/24v)
- Resistant to knocks, bumps and vibration
- Integral Fresnel lens for improved light output
- Selectable flash patterns via dipswitches
- Convertible power plug fits standard DIN or 'mini-DIN' power sockets
- Reliable in extreme temperatures (tested between -30°C and +50°C)
- Encapsulated electronics
- E-marked for road use
- Amber only

Part number	311.008/LED
Operating voltage	12-24 VDC
Current draw	1.8 A @ 12VDC
Mounting	Magnetic (70mph rated)
Type approval(s)	ECE Regulation 10 E9 - 10R 04 6919
Flash pattern(s)	Quad flash Double flash Rotating
Weight	1.8kg approx.
Dimensions	170mm (H) x 128mm (ø) (excluding cable/connector)





www.dun-bri.com

Dun-Bri Group Watermill Industrial Estate Aspenden Road Buntingford SG9 9JS

01763 274185 sales@dun-bri.com Dun-Bri Lancashire 58 Roman Way Ind. Est. Longbridge Road Preston PR2 5BE

01772 651647 lancashire@dun-bri.com 01924 577026 yorkshire@dun-bri.com

Dun-Bri Yorkshire 4 Eagle Point Wakefield 41 Ind. Est. Wakefield WF2 0XW

