H2-R



Product Name: H2-R Product Number: 700H2-R

Rechargeable headlamp with 82 + 420 Description lumens, red LED and twist style focus



Specifications

Light source

Charger output

Output 30 seconds (lumen)

Charging time (hours) Charging level indicator

Beam distance (m)

Charging port cover

Protection class

Charging port

Additional data

Run time (hours) down to 1 lumen

Beam width (cm) from 1 m distance

Operating temperature range (Celsius)

Cable for charger, ca. 1 m (supplied in box)

Run time (hours) down to 10% of full lumens

Housing ABS and aluminium Lens Acrylic, optical On/off switch Top, red rubber

1 x 18650: 3.7V - 2600mAh - 9.62Wh - Lithium Battery type

rechargeable battery 5W CREE XPG2-R4

Colour temperature (Kelvin) 7500K

Focus Twist style optical focus system Charger operating voltage Required: 100V-240V, 50-60Hz

Required: DC5V - 1A max (USB connector)

82 (low beam) / 420 (high beam) 16 (low beam) / 7 (high beam) 13.7 (low beam) / 4.2 (high beam)

1 x LED on battery compartment 60 (low beam) / 150 (high beam)

160 (flood) / 25 (spot)

IP65 / III -5°C to +40°C Micro USB Rubber, black

USB into charger, Micro USB into lamp Red LED: 8 lumens - 12 m beam distance



General Information

Lamp weight (ca.) 47 g and 163 g incl. battery Ø3.3 (cylinder) / 4.5 x 6.7 x 5.2 (housing) Lamp dimensions (ca.)

5703296700054 EAN code box (1 pc) 5703296710053 EAN code inner carton 5703296720052 EAN code outer carton Harmonized standard code 8513100000

Packaging

"PRO" design printed box Description Box size (ca.) 12.5 x 12 x 12.5 cm Box weight (ca.) 430 g

6 (inner carton) / 36 (outer carton) Carton quantity (pcs) Carton size 6 pcs. (ca.) 38 x 25.5 x 13.5 cm (inner carton) Carton size 36 pcs. (ca.) 41.3 x 39.5 x 53 cm (outer carton) Carton weight (ca.)

2.7 kg (inner carton) / 18.1 kg (outer carton)



Features

Rechargeable, lightweight headlamp with red LED and twist style focus

Charging indicator (1 x LED), red = charging / green = fully charged

Switch mode main light: low - high - off

Switch off at any stage (high or low beam) by holding down switch 2 sec. Switch on again at same stage

Battery compartment on back of the neck

Red LED on back of battery compartment. Separate switch. Switch mode: on - off

Cable in cold resistant PVC (down to -40 degrees)

Soft pad and high quality elastic strap (around and over head)

