




**This beacon is part of a range of LED warning beacons, which feature a dual-voltage SMD LED array with selectable flash patterns.**

- ◆ Dual-voltage operation (12/24v)
- ◆ Resistant to knocks, bumps and vibration
- ◆ Integral Fresnel lens for improved light output
- ◆ Selectable flash patterns via dipswitches
- ◆ Single bolt fixing allows cable to pass through mounting point making installation faster
- ◆ Reliable in extreme temperatures (tested between -30°C and +50°C)
- ◆ Encapsulated electronics
- ◆ E-marked for road use
- ◆ Amber only

Part number	311.009/LED
Operating voltage	12-24 VDC
Current draw	1.8 A @ 12VDC
Mounting	Single bolt (cable passes through mounting)
Type approval(s)	ECE Regulation 10 E9 - 10R 04 6919
Flash pattern(s)	Quad flash Double flash Rotating
Weight	1.8kg approx.
Dimensions	170mm (H) x 128mm (ø) (excluding cable/connector)



**www.dun-bri.com**

Dun-Bri Group  
 Watmill Industrial Estate  
 Aspenden Road  
 Buntingford SG9 9JS

01763 274185  
 sales@dun-bri.com

Dun-Bri Lancashire  
 58 Roman Way Ind. Est.  
 Longbridge Road  
 Preston PR2 5BE

01772 651647  
 lancashire@dun-bri.com

Dun-Bri Yorkshire  
 4 Eagle Point  
 Wakefield 41 Ind. Est.  
 Wakefield WF2 0XW

01924 577026  
 yorkshire@dun-bri.com

