

MODULE REPLACEMENT INSTRUCTIONS

! IMPORTANT ! - Read all instructions before replacing the modules.

! NOTE ! - Modules can be replaced without removing the lightbar from the vehicle.

COMPATIBLE PART CODES

308.R24CR65 / 308.R24CR65MAG / 308.R30CR65 /
308.R42CR65 / 308.R48CR65 / 308.R60CR65

! CAUTION ! - Disconnect the battery before replacing the module to prevent accidental shorting and/or electrical shock.


TOOLS REQUIRED

2.5mm Allen Key for side modules (NOT supplied)
3mm Allen Key for end modules (NOT supplied)

MODULE REPLACEMENT

308.R6MOD - SIDE MODULE

308.R8CMOD - END MODULE



1. Remove the screws relating to the desired module
2. Slide out the module you wish to replace
3. Unplug the module connector
4. Plug in the replacement module using the connector
5. Slide the replacement module into position
6. Fasten the removed screws to secure the module

MODULE LENS CLEANING

Occasional cleaning is recommended to ensure optimal light output.

Although tough, polycarbonate scratches easily, so take care when cleaning.

Clean lens with soap and water or a lens polish using a soft cloth.

! WARNING ! - Do NOT use solvents as they may damage the lens.

! WARNING ! - Do NOT use high-pressure washers or automatic car washers. This lightbar is rated IP67.