



This beacon is part of a range of LED warning beacons, which feature a dual-voltage SMD LED array with selectable flash patterns.

- ◆ Dual-voltage operation (12/24v)
- ◆ Resistant to knocks, bumps and vibration
- ◆ Integral Fresnel lens for improved light output
- ◆ Selectable flash patterns via dipswitches
- ◆ Fitted with three bolt flush mounting base for a clean installation
- ◆ Reliable in extreme temperatures (tested between -30°C and +50°C)
- ◆ Encapsulated electronics
- ◆ E-marked for road use
- ◆ Amber only

Part number	311.010/LED
Operating voltage	12-24 VDC
Current draw	1.8 A @ 12VDC
Mounting	Three bolt
Type approval(s)	ECE Regulation 10 E9 - 10R 04 6919
Flash pattern(s)	Quad flash Double flash Rotating
Weight	1.8kg approx.
Dimensions	170mm (H) x 140mm (ø) (excluding cable/connector)



www.dun-bri.com

Dun-Bri Group
 Watmill Industrial Estate
 Aspenden Road
 Buntingford SG9 9JS
 01763 274185
sales@dun-bri.com

Dun-Bri Lancashire
 58 Roman Way Ind. Est.
 Longbridge Road
 Preston PR2 5BE
 01772 651647
lancashire@dun-bri.com

Dun-Bri Yorkshire
 4 Eagle Point
 Wakefield 41 Ind. Est.
 Wakefield WF2 0XW
 01924 577026
yorkshire@dun-bri.com

