



This beacon is part of a range of halogen rotator warning beacons, which feature a dual-voltage motor assembly and are supplied with 12v and 24v bulbs at no extra cost.

- ◆ Dual-voltage motor (12/24v)
- Resistant to knocks, bumps and vibration
- Strengthened, UV-stabilised polycarbonate lens
- Worm-gear driven rotator assembly
- Power cables pass through mounting point for a quick, clean installation
- Reliable in extreme temperatures (tested between -30°C and +50°C)
- Chapter 8 compliant for highways work (requires two beacons to qualify)
- E-marked for road use
- Amber only

Part number	311.001
Operating voltage	12-24 VDC
Current draw	4.5 A @ 12VDC
Mounting	Single bolt (Cable passes through mounting)
Type approval(s)	ECE Regulation 10 E8 - 10R 02 08157 ECE Regulation 65 E8 - 65R TA1 00 1149
Flash pattern(s)	Rotating
Weight	2.0kg approx.
Dimensions	170mm (H) x 128mm (ø) (excluding cable/connector)







www.dun-bri.com

Dun-Bri Group Watermill Industrial Estate Aspenden Road Buntingford SG9 9JS

01763 274185 sales@dun-bri.com Dun-Bri Lancashire 58 Roman Way Ind. Est. Longbridge Road Preston PR2 5BE

01772 651647 lancashire@dun-bri.com Dun-Bri Yorkshire 4 Eagle Point Wakefield 41 Ind. Est. Wakefield WF2 0XW

01924 577026 yorkshire@dun-bri.com

