



WARNING LIGHTING | DIRECTIONAL LIGHTING | LIGHTBARS | WHITE LIGHTING | REVERSING SAFET



CAMERA SYSTEMS



DAC1003 7" LCD Colour System

This 4 camera capable camera system is with 7.0" monitor is designed to satisfy the needs of all commercial vehicle operators whether they be a goods vehicle, tow truck, farm equipment or construction machinery.

Features and Benefits

- Standard colour camera
- Four camera expandable

Monitor

- 7.0" TFT LCD Wide Angle
- No. Languages: 11
- Auto Backlit Buttons
- Brightness Control: Automatic or Manual (selectable)
- Resolution (Pixels): 1440(H) x 234(V)
- Power Consumption: 25W
- Power Inputs: 12-32Vdc
- Anti Vibration: 5g
- Operating Temp: -20°C to +65°C
- Dimensions WxHxT(mm): 182 x 122 x 26
- Weight: 1.85kg
- Certificates: CE, FCC, EMARK
- Four trigger signal inputs, auto switch to the working camera
- 16:9 Aspect Ratio
- Trigger wire for dual picture, relative camera can be combined optionally
- Quad/dual picture priority can be selected
- Reversing distance grid and left/right turning indicator arrow on the screen
- AV input for DVD
- Line video: output. Connected monitor can display synchronously
- REC video output, and picture can be single or split
- Auto-controlled day and night brightness mode
- Single, dual, tribal, quad image

Camera

- Colour
- Effective Pixels: 512 x 582
- Current Consumption: 400mA (max)
- Power Supply: 12Vdc (from monitor)
- Operating Temp: -20°C to +70°C
- Lens angle: 180°
- IP67
- Night Vision Distance: 10m
- Front Speaker
- No. Infra-red Lights: 12
- · Day/Night Sensor
- Microphone
- Connection: RCA/4 pin DIN
- Anti Vibration: 10g
- Weight: 0.5kg
- Certificate: CE, FCC, R10

+44 (0)113 237 5340 | sales@eccogroup.com